

newline

S ELITE SERIES

Beyond Display. Beyond Expectations.

Powerful. Intelligent. Future-Ready. S-Elite sets a new benchmark for interactive Displays.

New
Launch



ANDROID

16



128 GB* Internal Storage



8 GB RAM



GOOGLE
EDLA CERTIFIED



OFFICIAL
GOOGLE PLAYSTORE



Resolution

3840 x 2160 (4K)



Colors

1.07 Billion



Color Depth

10 bit (8 bit+FRC)



Brightness

max upto ≥ 500 cd/m²



Response Time(Typ.)

4ms



Display Life Time

>50,000 hours

*Terms and Condition apply

MODEL	TT-6526S	TT-7526S	TT-8626S
DISPLAY			
Active Screen Size	65"	75"	86"
Screen Type	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)	LCD (Direct LED Backlight)
Display Area	1428.48mm (H) x 803.52mm (V)	1650.24mm(H) x928.26mm(V)	1895.04mm(H) x1065.96mm(V)
Display Ratio	16:9	16:9	16:9
Resolution	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)
Refresh Rate	120 Hz	120 Hz	120 Hz
Colors	1.07 Billion	1.07 Billion	1.07 Billion
Color Depth	10 bit (8 bit+FRC)	10 bit (8 bit+FRC)	10 bit (8 bit+FRC)
Brightness	>=400 cd/㎡	>=450 cd/㎡	>=500 cd/㎡
Colour gamut	NTSC 72%	NTSC 72%	NTSC 72%
Contrast Ratio	15000:1	15000:1	15000:1
Response Time(Typ.)	4ms	4ms	4ms
Viewing Angle	178°	178°	178°
Display Life Time	>50,000 hours	>50,000 hours	>50,000 hours
SMART SYSTEM			
Chipset	MTK-G520	MTK-G520	MTK-G520
CPU	2*A78 2.2Ghz + 6*A55 2.0Ghz (Octa Core)	2*A78 2.2Ghz + 6*A55 2.0Ghz (Octa Core)	2*A78 2.2Ghz + 6*A55 2.0Ghz (Octa Core)
GPU	G57 MC2 880Mhz	G57 MC2 880Mhz	G57 MC2 880Mhz
NPU	9 Tops	9 Tops	9 Tops
RAM	8 GB	8 GB	8 GB
ROM	64 GB	64 GB	64 GB
ON Board TF Card	64 GB*	64 GB*	64 GB*
Android Version	Android 16	Android 16	Android 16
OS Version	EDLA	EDLA	EDLA
OPS Slot	Support 4K	Support 4K	Support 4K
WiFi Module Model	WiFi 6: 2.4 G+5 G	WiFi 6: 2.4 G+5 G	WiFi 6: 2.4 G+5 G
Wi-Fi Standard	IEEE 802.11a/b/g/n/ac/ax	IEEE 802.11a/b/g/n/ac/ax	IEEE 802.11a/b/g/n/ac/ax
Bluetooth	BT 5.2	BT 5.2	BT 5.2
AV INTERFACE			
Front I/O	1 x Type C (PD 65 W, full functions)	1 x Type C (PD 65 W, full functions)	1 x Type C (PD 65 W, full functions)
Front I/O	1 x HDMI In (2.1, 4K@60 Hz) HDCP 2.3	1 x HDMI In (2.1, 4K@60 Hz) HDCP 2.3	1 x HDMI In (2.1, 4K@60 Hz) HDCP 2.3
Front I/O	1 x USB Touch 3.0	1 x USB Touch 3.0	1 x USB Touch 3.0
Front I/O	2 x USB 3.2 Gen 1	2 x USB 3.2 Gen 1	2 x USB 3.2 Gen 1
Front I/O	1 x Mic In (3.5 mm Mini Jack)	1 x Mic In (3.5 mm Mini Jack)	1 x Mic In (3.5 mm Mini Jack)
Rear I/O	2 x HDMI In (2.1, 4K@60 Hz) HDCP 2.3	2 x HDMI In (2.1, 4K@60 Hz) HDCP 2.3	2 x HDMI In (2.1, 4K@60 Hz) HDCP 2.3
Rear I/O	1 x DP 1.2 (4K@60Hz)	1 x DP 1.2 (4K@60Hz)	1 x DP 1.2 (4K@60Hz)
Rear I/O	1 x Type C (upto 15 W, full functions)	1 x Type C (upto 15 W, full functions)	1 x Type C (upto 15 W, full functions)
Rear I/O	2 x USB 3.2 Gen 1 Public	2 x USB 3.2 Gen 1 Public	2 x USB 3.2 Gen 1 Public
Rear I/O	2 x USB Touch 3.0	2 x USB Touch 3.0	2 x USB Touch 3.0
Rear I/O	1 x HDMI Out (2.1, 4K@60 Hz) HDCP 2.3	1 x HDMI Out (2.1, 4K@60 Hz) HDCP 2.3	1 x HDMI Out (2.1, 4K@60 Hz) HDCP 2.3
Rear I/O	1 x S/PDIF Out	1 x S/PDIF Out	1 x S/PDIF Out
Rear I/O	1 x Line Out	1 x Line Out	1 x Line Out
Rear I/O	1 x RS232	1 x RS232	1 x RS232
Rear I/O	1 x VGA In	1 x VGA In	1 x VGA In
Rear I/O	1 x VGA Audio In	1 x VGA Audio In	1 x VGA Audio In
Rear I/O	1 x LAN In 10/100/1000	1 x LAN In 10/100/1000	1 x LAN In 10/100/1000
Rear I/O	1 x LAN Out 10/100/1000	1 x LAN Out 10/100/1000	1 x LAN Out 10/100/1000
SPEAKER			
Speaker Position	Bottom Front	Bottom Front	Bottom Front
Speaker Power (Max.)	20Wx2	20Wx2	20Wx2
Speaker Rated Impedance	6Ω	6Ω	6Ω
Speaker Freq.Response	100Hz-10KHz SPL -10dB	100Hz-10KHz SPL -10dB	100Hz-10KHz SPL -10dB
Output S.P.L.	80±3dB	80±3dB	80±3dB
TOUCH TECHNOLOGY			
Glass Surface Treatment	Anti-Glare	Anti-Glare	Anti-Glare
Touch resolution	32,768 x 32,768 px	32,768 x 32,768 px	32,768 x 32,768 px
Glass Hardness	MoHS 7; 9H pencil	MoHS 7; 9H pencil	MoHS 7; 9H pencil
Glass Thickness	3.2 mm	3.2 mm	3.2 mm
Glass Transparency	88%±3	88%±3	88%±3
Glass Haze	4-8%	4-8%	4-8%
Bonding Type	Zero bonding	Zero bonding	Zero bonding
Touch Soluttion	IR	IR	IR
Touch Accuracy	±0.5mm (90% of center part)	±0.5mm (90% of center part)	±0.5mm (90% of center part)
Touch Scan Rate	600Hz	600Hz	600Hz
Touch Points	50 Touch points Windows; 50 Touch points Android	50 Touch points Windows; 50 Touch points Android	50 Touch points Windows; 50 Touch points Android
Real Palm rejection	Supported	Supported	Supported
Wake on LAN	Supported	Supported	Supported
IP Control	Supported	Supported	Supported
ELECTRICAL PARAMETERS			
Working Voltage	AC 100-240V	AC 100-240V	AC 100-240V
Working Power Consumption	150 W	240 W	270 W
Power Consumption (Standby Mode)	< 0.5 W	< 0.5 W	< 0.5 W
Storage Temperature&Humidity	-20~60°C 0~90%RH (non-condensing)	-20~60°C 0~90%RH (non-condensing)	-20~60°C 0~90%RH (non-condensing)
Working Temperature/Humidity	0~40°C 20~80%RH (non-condensing)	0~40°C 20~80%RH (non-condensing)	0~40°C 20~80%RH (non-condensing)
Installation Method (optional)	wall-mounted / mobile stand	wall-mounted / mobile stand	wall-mounted / mobile stand