

# INTERACTIVE WHITEBOARD



MODEL NO	IR30-82S	MODEL NO	IR30-82S
TECHNOLOGY	IR	SCAN RATE	125dot/Second
ACTIVE AREA SIZE(“)	78.8”	INTERFACE	USB
ACTIVE AREA SIZE(MM)	1641*1148	USB TYPE	A-B
PROJECTION SIZE(“)	74.7”	USB LENGTH IN STANDARD PACKAGE	5m
PROJECTION AREA *(MM)	1518*1138	POWER CONSUMPTION (W)	<0.5W
ASPECT RATIO	4:3	DRIVER SUPPORT OS	Windows 7, 8 & 10 32bit & 64 bit
HOT KEYS	Two sides	MAC & LINUX	Driver available upon request
FRAME TYPE	Alloy Frame	OPERATION TEMPERATURE(°C)	-15-50°c
MULTI - TOUCH	4 or 10 points	OPERATION HUMIDITY (%)	20~90%
INPUT	Finger or pen	STORAGE TEMPERATURE (°C)	-40-50°c
PEN TRAY	Simple Pen Holder	STORAGE HUMIDITY (%)	10~95%
RESOLUTION	32767*32767	RESPONSE TIME	25ms @first touch, 8ms after 1st touch
LXWXH (MM)	1710*1217*44.5		



**Pen Writable**  
Surface



**Robust**  
Design



**Work With Different**  
Platforms



**Optional Ceramic**  
Surface



**Patented I-AVST Infra**  
Ray (IR) Multi Touch



**4:3 and**  
16:10



**Eco**  
Friendly



**Support 10**  
Points Touch