

newline



NT+ SERIES PRODUCT SPECIFICATIONS

MODEL	TT-5523NT	TT-6523NT	TT-7523NT	TT-8623NT	TT-9823NT
Display					
Active Screen Size	55"	65"	75"	86"	98"
Display Area	1210 × 681mm	1429 × 804 mm	1651 × 929mm	1896 × 1066mm	2159 × 1214mm
Backlight	LED	LED	LED	LED	LED
Display Ratio	16:9	16:9	16:9	16:9	16:9
Resolution	3840 × 2160 (4K)	3840 × 2160 (4K)	3840 × 2160 (4K)	3840 × 2160 (4K)	3840 × 2160 (4K)
Display Colors	1.07G (8 bit + FRC)	1.07G (8 bit + FRC)	1.07G (8 bit + FRC)	1.07G (8 bit + FRC)	1.07G (8 bit + FRC)
Brightness	400 cd/m ²	400 cd/m ²	450 cd/m ²	450 cd/m ²	500 cd/m ²
Contrast	Typ. 4000:1	Typ 5000:1	Typ 5000:1	Typ 5000:1	Typ 5000:1
Response Time	8 ms (typ.)	8 ms (typ.)	8 ms (typ.)	8 ms (typ.)	8 ms (typ.)
Viewing Angle	178°	178°	178°	178°	178°
Life Time	≥50000 hours	≥50000 hours	≥50000 hours	≥50000 hours	≥50000 hours
Electricity					
Working Voltage	AC100-240V Max. 2.5A	AC100-240V Max. 3.0A	AC100-240V Max. 3.0A	AC100-240V Max. 3.5A	AC100-240V Max. 5.5A
Power Consumption (Standard Mode)	250W	300W	300W	350W	550W
Power Consumption (Standby mode)	<0.5W	<0.5W	<0.5W	<0.5W	<0.5W
Speaker					
Speaker position	Downward	Downward	Downward	Downward	Downward
Rated Impedance	6Ω	6Ω	6Ω	6Ω	6Ω
Freq.Response	200Hz-20KHz SPL -10dB	250Hz-20KHz SPL -10dB	250Hz-20KHz SPL -10dB	250Hz-20KHz SPL -10dB	250Hz-20KHz SPL -10dB
Output S.P.L.	80±3dB	80±3dB	80±3dB	80±3dB	80±3dB
Max.Power Output	15W × 2	20W × 2	20W × 2	20W × 2	20W × 2
Transportation/ Storage					
Storage Temperature/Humidity	15 °C ~45 °C / 20~90% RH (Non coagulation)	15 °C ~45 °C / 20~90% RH (Non coagulation)	15 °C ~45 °C / 20~90% RH (Non coagulation)	15 °C ~45 °C / 20~90% RH (Non coagulation)	15 °C ~45 °C / 20~90% RH (Non coagulation)
Working Temperature/Humidity	0 °C~40 °C / 20~80% RH (Non coagulation)	0 °C~40 °C / 20~80% RH (Non coagulation)	0 °C~40 °C / 20~80% RH (Non coagulation)	0 °C~40 °C / 20~80% RH (Non coagulation)	0 °C~40 °C / 20~80% RH (Non coagulation)
Installation Method (optional)	wall-mounted, mobile cart	wall-mounted, mobile cart	wall-mounted, mobile cart	wall-mounted, mobile cart	wall-mounted, mobile cart
"Outline Dimension (without wall mount bracket thickness) "	1260 × 731 × 71 mm	1479 × 854 × 92 mm	1701 × 979 × 94 mm	1946 × 1116 × 94 mm	2213 × 1293 × 88 mm
Packing Dimension	1378 × 185 × 840 mm	1604 × 207 × 977 mm	1819 × 227 × 1095 mm	2075 × 250 × 1230 mm	2370 × 1484 × 356 mm
Net Weight	18±2kg	24±2kg	33±2kg	42±2kg	73±2kg
Gross Weight	25±2kg	34±2kg	46±2kg	59±2kg	93±2kg
VESA Mount installation position	400 × 400 mm	600 × 400 mm	800 × 400 mm	800 × 400 mm	800 × 600 mm
Smart System					
Chipset	T982	T982	T982	T982	T982
CPU	Quad core ARM Cortex-A55 1.5GHz,Max.1.9GHz	Quad core ARM Cortex-A55 1.5GHz,Max.1.9GHz	Quad core ARM Cortex-A55 1.5GHz,Max.1.9GHz	Quad core ARM Cortex-A55 1.5GHz,Max.1.9GHz	Quad core ARM Cortex-A55 1.5GHz,Max.1.9GHz
GPU	ARM Mali-G52 MP2 (2EE)	ARM Mali-G52 MP2 (2EE)	ARM Mali-G52 MP2 (2EE)	ARM Mali-G52 MP2 (2EE)	ARM Mali-G52 MP2 (2EE)
RAM	4G	4G	4G	4G	4G
ROM	32G	32G	32G	32G	32G
Android Version	13 (64bit)	13 (64bit)	13 (64bit)	13 (64bit)	13 (64bit)
Multimedia File Formats Support	"Image: .jpg, .bmp, .png Video: .mkv/.wmv/.avi/.mp4/ .mpg/.mpeg/.mov/.dat/.iso Audio: .mp3/.wma/.m4a/.mp4/ .aac" Support Portrait Mode	"Image: .jpg, .bmp, .png Video: .mkv/.wmv/.avi/.mp4/ .mpg/.mpeg/.mov/.dat/.iso Audio: .mp3/.wma/.m4a/.mp4/ .aac" Support Portrait Mode	"Image: .jpg, .bmp, .png Video: .mkv/.wmv/.avi/.mp4/ .mpg/.mpeg/.mov/.dat/.iso Audio: .mp3/.wma/.m4a/.mp4/ .aac" No	"Image: .jpg, .bmp, .png Video: .mkv/.wmv/.avi/.mp4/ .mpg/.mpeg/.mov/.dat/.iso Audio: .mp3/.wma/.m4a/.mp4/ .aac" No	"Image: .jpg, .bmp, .png Video: .mkv/.wmv/.avi/.mp4/ .mpg/.mpeg/.mov/.dat/.iso Audio: .mp3/.wma/.m4a/.mp4/ .aac" No
Others					
Speciality	Pluggable WiFi module wifi 5 + wifi 6 +BT 5.2				
Wifi module	Support				
Multi-language	Support				
Firmware update	USB / OTA				
Standby mode	Support				
Back button	Power, Up, Down, Left, Right, OK, Return, Menu				
AV Ports					
Rear input port	Type A USB 2.0 x 3, HDMI IN x 2, HDMI IN(ARC) x 1, LAN INx1 RS232x1, Type C(USB 2.0/4K 60Hz/PD15w), DP x 1				
Rear output port	HDMI OUT x 1 LAN OUT x1 S/PDIF OUTx1 LINE OUT(3.5mm) x 1				
OPS Slot	N/A				

newline

1-800-419-0309

www.newlineinteractive.in

Chennai

Room No. 202, 203, 211
No.37, Workafella, TTK Road, Alwarpet,
Chennai-600018, Tamil Nadu

Gujarat

104, 1st Floor, Shilp Arista, Opposite
Stellar, Sindhu Bhavan Road, Thaltej,
Ahmedabad 380015, Gujarat

Delhi

Unit No. A-717, 7th Floor,
DLF Tower A, Jasola District Centre,
New Delhi- 110025

Kolkata

RAIKVA Tower 3A, Ram Mohan
Mullick Garden Lane, 3rd Floor, Suit No - 309
Kolkata, West Bengal 700010

Mumbai

1st Floor,B-107, Kanakia Wall Street,
Chakala, Andheri Kurla Road,
Andheri East Mumbai-400059, Maharashtra.

Hyderabad

6-3-871, Ground Floor, Snehalatha
Building , Greenlands Rd, Begumpet,
Hyderabad, Telangana 500016