

SPECIFICATIONS

Model	TT-6518RS	TT-7518RS	TT-8618RS	TT-9818RS
Display				
Active Screen Size	65"	75"	86"	98"
Backlight	LED			
Display Area	1432 × 807 mm	1652 × 930 mm	1893 × 1069 mm	2162 × 1217 mm
Display Ratio	16:9			
Resolution	3840 × 2160 Pixels			
Display Color Depth	8-bit	8-bit	10-bit	10-bit
Brightness	370 nit			500 nit
Contrast Ratio	4000:1	4000:1	4000:1	4000:1
Response Time	8 ms			
Viewing Angle	178°			
Life Time	≥ 30,000 hours			
Power				
Power Consumption	Maximum ≤ 250 W Standby Mode ≤ 0.5 W	Maximum ≤ 400 W Standby Mode ≤ 0.5 W	Maximum ≤ 450 W Standby Mode ≤ 0.5 W	Maximum ≤ 700 W Standby Mode ≤ 0.5 W
Working Voltage	AC 100-240 V, 50/60 Hz			
Touch				
Touch Surface	Anti-Glare Glass			
Transparency	> 88%			
Haze	2% - 5%			
Surface Hardness	7H			
Touch Technology	Infrared Touch			
Touch Points	20 Points in Windows/ 10 Points in Android			
Writing Tools	Passive Pen/ Finger/ Palm			
Positioning Accuracy	±2 mm	±2 mm	±2 mm	±3 mm
Communication Interface	USB-A			
Speaker				
Speaker Position	Front			
Rated Impedance	8 Ω			
Frequency Response	180 - 20K Hz	180 - 20K Hz	180 - 20K Hz	90(±20%) - 20K Hz
Max. Power Output	15 W × 2	15 W × 2	15 W × 2	18 W × 2
Environmental/ Physical Specifications				
Storage Temperature/ Humidity	-15 - 55 / 20 - 90% RH			
Working Temperature/ Humidity	0 - 40 / 20 - 80% RH			
Mounting (Optional)	Wall Mount/ Floor Stand			
Outline Dimensions	1546 × 944 × 96 mm	1770 × 1071 × 109 mm	2019 × 1212 × 109 mm	2256 × 1361 × 105 mm
Packing Dimensions	1695 × 1075 × 275 mm	1920 × 1195 × 275 mm	2170 × 1345 × 275 mm	2460 × 400 × 1625 mm
Net Weight	44 kg	56 kg	73 kg	133 kg
Gross Weight	57 ± 2 kg	71 ± 2 kg	91 ± 2 kg	233 ± 2 kg
VESA Mount Installation Position	600 × 400 mm	800 × 400 mm	800 × 400 mm	800 × 400 mm
Intelligent Thermo-Protector	Yes			
OPS PC	Available			
Wi-Fi Dongle	Available			
Trucast Express (Screen Sharing)	Available			
Connectivity				
Front Interface Inputs	HDMI 1.4 × 1, USB(Touch) × 1, USB(Dynamic) × 2, MIC × 1			
Rear AV Inputs	HDMI 2.0(4K@60Hz) × 2, DP 1.2(4K@60Hz) × 1, VGA(1920x1080@60Hz) × 1, PC Audio × 1, USB(Touch) × 4			
AV Outputs	HDMI Out (Support 4K@60Hz) × 1			
Other	USB 2.0(Dynamic) × 1, USB 3.0(Dynamic) × 1, USB 2.0 Embedded × 1, RS232 × 1, RJ45 × 2, OPS Slot(4K@60Hz) × 1, DC 5V-2A Out, Line Out × 1, SPDIF Out × 1			

* All specifications are subject to change without further notice.

TRU TOUCH *RS* Series



HASSLE-FREE INTERACTIVE DISPLAY FOR CLASSROOMS

Redefine smarter collaboration

Bring your own device

4K UHD display for clear and vivid images

Multi-touch interaction

65" 75" 86" 98"

