

newline



newline **STV SERIES**

43"

55"

65"

75"

85"


98"

Next-generation Borderless *Non-touch* Display

The Newline STV Serie is the next-generation non-touch display; 4K HD resolution, 1 mm ultra-thin bezel, and High Dynamic Range offer users an immersive audiovisual experience.

Team Collaboration with wireless casting connectivity allows users to share their ideas with Windows, Mac, Android, and iPhone in the classroom, huddle room, and conference room with simplicity.

Newline STV is equipped with HDMI signal detection, enabling quick and automatic switching connection. Users can also access Word, spreadsheet, and embedded document files from USB flash drives, enhancing convenience and flexibility.



Ultra-thin
Bezel



High Screen
Display Ratio



4K HD



178°
View Angle



Pure
Color



Remote
Control

Without TV Tuner Card

	STV-4324	STV-5524	STV-6524	STV-7524	STV- 8524	STV-9824
Display						
Active Screen Size	43"	55"	65"	75"	85"	98"
Display Area	941 x 529 mm	1210 x 680 mm	1428 x 804 mm	1650 x 928mm	1872 x 1053 mm	2159 x 1214 mm
Display Type	LCD					
Back Light Unit	Direct LED					
Display Ratio	16:9					
Resolution	4K 3840 x 2160					
Response Time	4ms					
Refreshing Frequency	120 Hz					
Display Color	1.07 Billion 10 bit + FRC					
Brightness	450 nits	500 nits	550 nits	550 nits	600 nits	650 nits
Contrast Ratio (Typ.)	15000:1				15000:1	15000:1
Viewing Angle	178°					
Operation Time	24 x 7					
Electrical Parameter						
Working Voltage	100-240 V~ 50/60 Hz					
Power Consumption (Standard Mode)	90W	140W	170W	260W	310W	475W
Power Consumption (Standby Mode)	≤0,5 W					
Speaker						
Speaker Position	Bottom front					
Power Output	2 x 10 W				2 x 15 W	
Ports						
Rear input port	HDMI In 2.0 x 1 (ARC) , HDMI in 2.0 x 2 , USB-A 2.0 x 1,USB-A 3.0 x 1,LAN In (RJ45) x 1,AV In x 1					
Rear output port	S/PDIF Out x 1, Audio Output (Jack 3.5 mm) x 1					
Smart System						
Embedded system	Android 11					
CPU	ARM Cortex-A55 x 4					
GPU	ARM Mali-G31 MC2					
RAM	2 GB					
Storage	16 GB					
Wi-Fi / Bluetooth	Wi-Fi 5, Bluetooth					
Transportation / Storage						
Storage Temperature/Humidity	-20~60°C 0~85%RH (non-condensing)					
Working Temperature/Humidity	0~40°C 20~80%RH (non-condensing)					
Outline Dimension (without bracket/stand)	957x559x86 mm	1226x709x87 mm	1446x831x85 mm	1668x956x88 mm	1890x1081x91 mm	2182x1255x113 mm
Packaging Dimension	1075x142x652 mm	1350x144x837 mm	1600x164x960 mm	1840x190x1103 mm	2030x192x1250 mm	2390x1500x280 mm
Net Weight	6.3kg	10.9kg	16.6kg	22.7kg	29.5kg	74.0kg
Gross Weight	9.0kg	15.7kg	23.5kg	34.3kg	42.4KG	105.0kg
Wall-hanging Screw	M6 x 12 mm	M6 x 20mm				
VESA Mount Installation Position	300 x 300 mm	400 x 300 mm			500 x 400 mm	
Accessories						
Power Cord By Region	1.5 m					
Remote Control	1 (with AAA Battery 2 set)					