

TRUTOUCH RS65+



NEXT GENERATION 4K INTERACTIVE DISPLAYS



Android 8.0.0



RAM

3 GB



ROM 16 GB (Upto 64 GB)



450 cd/m² **Brightness**

"Flicker Free" Certified by






Present wirelessly from any network with a single click. Share video, links, and files from any device.



Broadcast content or present wirelessly from a personal device, and invite up to 200 participants to connect from their own.







PRODUCT SPECIFICATION

MODEL NAME	TT-6519RS	POWER CONSUMPTION	
ACTIVE SCREEN SIZE ("INCH)	65"	POWER CONSUMPTION	Maximum ≤250W Standby Mode ≤0.5W
DISPLAY BACKLIGHT	DLED	WORKING VOLTAGE	AC 100-240V, 50/60Hz
DISPLAY AREA	1432*807MM	TOUCH	
DISPLAY RATIO	16:9	TOUCH SURFACE MATERIAL	TOUGHENED TEMPERED GLASS
RESOLUTION	3840*2160	TOUCH SURFACE TECHNOLOGY	ANTI-GLARE GLASS
DISPLAY COLORS	10 BIT	PROTECTION	3M ANTIGLARE
LCD BRIGHTNESS	>450CD/M2	TRANSPARENCY	>88%
CONTRAST RATIO (TYPICAL)	15000:1	HAZE	2%~5%
RESPONSE TIME (TYPICAL)	4MS	TOUCH SURFACE HARDNESS	H7
VIEWING ANGLE	178°	TOUCH SENSOR	INFRARED TOUCH
LIFE TIME (WORKING HOURS)	>50,000 HOURS	TOUCH POINTS	20 POINTS UNDER WINDOWS 10 POINTS UNDER ANDROID
DISPLAY ORIENTATION	LANDSCAPE	TOUCH SCREEN WRITING TOOLS	NANO PEN (>3MM WIDTH) INCLUDED OR FINGER
REFERENCE FREQUENCY	120HZ	TOUCH RESPONSE TIME	≤4MS
		POSITIONING ACCURACY	±1MM
ANDROID SMART SYSTEM		TRANSMISSION RANGE	5M
CHIPSET	MTK8386	COMMUNICATION INTERFACE	USB
CPU	ARMV8 A73*2+A53*2 (A53 : 1.05-1.3GHZ; A73 : 1.15-1.5GHZ)	To proper the second se	038
GPU	MALI-G51MP2 650 MHZ	SPEAKER	
RAM	3GB	SPEAKER POSITION	FORWARD
ROM	16GB BUILD IN (UPTO 64GB)	SPEAKER RATED IMPEDANCE	80
EXTERNAL MEMORY	32GB TF CARD (BUILD IN)	SPEAKER FREQ.RESPONSE	180HZ-20KHZ
TOTAL IN-BUILT MEMEORY	48GB (INBUILT TF CARD SLOT SUPPORT MAX 64GB)	SPEAKER MAX.POWER OUTPUT	15W*2
ANDROID VERSION	8.0.0	TRANSPORTATION/STORAGE	
ANDROID RESOLUTION	4K	STORAGE TEMPERATURE/HUMIDITY	-15"~55"/20" 90" RH(NON COAGULATION)
INTELLIGENT THERMAL PROTECTOR	AUTOMATIC HIBERNATE WHEN OVER HEATED	WORKING TEMPERATURE/HUMIDITY	0 °-40° /20° 80° RH(NON COAGULATION)
WIFI DONGLE	AVAILABLE	INSTALLATION METHOD (OPTIONAL)	WALL-MOUNTED / FLOOR STAND
GUI - GRAPHIC USER INTERFACE	THE DISPLAY MUST HAVE GUI FOR EASE ACCESS OF RESOURCES, FUNCTIONS AND SHORTCUTS. THIS GUI SHALL BE ANY PROPRIETARY OS BUT MUST BE COMPUTABLE WITH ANDROID CODING.		
		OUTLINE DIMENSION (WITHOUT WALL MOUNT BRACKET THICKNESS)	1546*944*96MM
		PACKING DIMENSION	1670X1056X221MM
		NET WEIGHT	APPROX.44KG
		VESA MOUNT	600X400MM
DISCUSSION / WHITE BOARD	BUILD-IN WHITE BOARD (SEAMLESS WRITING)WITH DIFFERENT SIZE OF PEN THICKNESS, BUILT-IN OPTION TO IMPORT PICTURE AND ANNOTATE OVER ON THAT.BUILT-IN OPTION TO ACCESS BROWSER IN ANDROID WHITEBOARD	GROSS WEIGHT	57±2KG
		ANDROID SMART SYSTEM	
		CUSTOMIZED GUI	USER CAN EASILY CUSTOMIZED THEIR
NEWLINE CAST	(A WIRELESS PRESENTATION SOFTWARE COMES WITH INBUILT FOR IN ROOM PRESENTATION MAXIMUM CONNECTIVITY OF BYOD DEVICES - 4 / 8 USERS (ANDROID 4 USER / WIN 6 USER) CONTROL - THE SETUP SHOULD BE IN SUCH A WAY THAT THE		OWN BACKGROUND AND LOGO'S
		MULTIMEDIA FILE FORMATS SUPPORTED	SUPPORT ALL MAJOR TYPES OF MULTI-MEDIA FILES
			THIS PRODUCT SUPPORTS OBJECT RECOGNITION AND PRODUCES DIFFERENT EFFECTS ACCORDING TO THE
	PRESENTER SHOULD HAVE CONTROL OF THE GUI OF THIS REMOTE INTERACTIVE PRESENTATION KIT FROM THE TOUCH INTERACTIVE FLAT	OBJECT RECOGNITION	DIAMETER AND SIZE OF THE INPUT OBJECTS. • FIST/PALM: IDENTIFIED AS AN ERASER (100 PT).
	PANEL DISPLAY DISPLAY CAPABILITY - EQUIPMENT SHOULD HAVE CAPABILITY TO DISPLAY 4 /8 SOURCES AT A TIME SYSTEM SUPPORTED - WIN/MAC/IOS/ANDROID)		 FINE PEN (3MM): SUGGESTED TO USE WHILE WRITING.
			 THICK PEN (≥ 8 MM)/ FINGER: SUGGESTED TO USE WHEN YOU WAN TO HIGHLIGHT
		SMART EYE PRODUCTION	SMART EYE PROTECT KEEP YOUR EYE VISION
NEWLINE DISPLAY MANAGEMENT	CENTRALLY MANAGE ALL YOUR INTERACTIVE DISPLAYS: EASILY MANAGE AND DEPLOY APPS, CONFIGURE DISPLAY SETTINGS, ADD LICENCES, USE DIGITAL SIGNAGE FEATURES OR BROADCAST EMERGENCY MESSAGES TO ALL NEWLINE INTERACTIVE DISPLAYS, WITHOUT EVER HAVING TO LEAVE YOUR DESK.		SAFE FROM IFPD'S LIGHT BLUE LIGHT CONTRIBUTES TO DIGITAL EYE STRAIN: IFPD'S GLASSES
		BLUE LIGHT FILTER	THAT BLOCK BLUE LIGHT MAY INCREASE COMFORT FOR USERS
		OTA (OVER-THE-AIR) UPDATE	UPGRADE THE LATEST FIRMWARE FOR YOUR DISPLAYS THROUGH OUR OTA UPDATE SUPPORT AND KEEP THEMRUNNING SMOOTHLY AT ALL
			TIMES
NEWLINE BROADCAST	SHARE CONTENT TO AUDIENCES OF ANY SIZE HASSLE-FREE BROADCAST IS BROADCAST WEBPAGE AND SHARE YOUR SCREEN IN REAL-TIME FROM YOUR NEWLINE DISPLAY TO ANY PARTICIPANT CONNECTED. EASILY INVITE UP TO 200 PARTICIPANTS TO CONNECT THEIR OWN DEVICE FROM THE MEETING ROOM, CLASSROOM, LECTURE THEATER OR ANY OTHER PLACE IN THE WORLD WITH A NETWORK CONNECTION.	OPS PC	AVAILABLE
		AV PORTS	
		FRONT INTERFACE INPUTS	HDMI 1.4 1, USB(TOUCH) X 1, USB(PUBLIC) X 2, MICX1
		THOM INTERVACE IN OTO	HDMI 2.0(4K@60HZ*2) X 2, DP1.2(4K@60HZ) X 1, VGA
		REAR AV INPUTS	(1920X1080@60HZ)X1 & PC AUDIOX1 , USB(TOUCH) X 4
	THE ONBOARD SYSTEM SUPPORTSANNOTATION, SAVING		
OTHER PERSONS	AND SEND EMAIL OF ANNOTATION FILES AND SELECTING THE INPUTS AND CHANGING THE VOLUME . SCHEDULING	OTHER	USB2.0(PUBLIC) X 1,USB3.0(PUBLIC) X 1, USB 2.0 EMBEDDED X 1, RS232 X 1, RJ45 X 2, OPS
OTHER FEATURES	FUNCTION FOR MEETING ROOM SCHEDULES, BUILDIN	UITER	SLOTS(4K@60HZ) X 1,DC 5V-2A OUT, LINE OUT X1, SPDIF OUT X1
	WIFI(2.4G/59) AND SO ON		IMAGE: JPEG, BMP, PNG VIDEO: MPEG1, MPEG2, MPEG4,
FILE COMMANDER	HELPS TO EASILY OPEN YOUR USB DRIVE AND ACCESS YOUR DOCUMENTS / FILES. ADDITIONAL FEATURES IN FILE COMMANDER: ADD CLOUD: CLOUID BASED FILE STORAGE SERVICES ARE AVAILBALE. USER CAN DIRECTLY DOWNLOAD THEIR DOCUMMETS OF FILES AND ACCESS DURING PRESENTATION. FFP: FILE TRANSFER PROTOCOL (FTP) IS THE COMMONLY USED PROTOCOL FOR EXCHANGING FILES OVER THE INTERNET LOCAL AREA NETWORK: A LOCAL AREA NETWORK (LAN) IS A GROUP OF COMPUTERS AND ASSOCIATED DEVICES THAT SHARE A COMMON COMMUNICATIONS LINE OF WIRELESS LINK TO A SERVER.		SORENSONH.263,H.263,H.264,HEVC/H.265,MVC,
		MULTIMEDIA FILE FORMATS SUPPORT	AVS,AVS+,WMV3,VC1,MOTION JPEG,VP8,VP9,RV30/RV40 AUDIO:MPEG1/2
			@LAYER1;@LAYER2;@LAYER3,EAC3,ACC-LC,HEAAC,VORBIS,LPCM,
			IMA-ADPCM,MS-ADPCM,G711 A/MU-LAW,LBR(CODK),FLAC
		CERTIFICATES	
		REGULATIONS	ROHS, EMC, FCC, LVD
		TUV RHEINLAND CERTIFIED	YES
	COMMUNICATIONS LINE OR WIRELESS LINK TO A SERVER. PRE LOADED AQUA MAIL - YOU CAN EASILY EMAIL YOUR	101 MIEMONIO CENTILIEO	
EMAIL SUPPORT	PRE LOADED AQUA MAIL - YOU CAN EASILY EMAIL YOUR WHITEBOARD CONTENT TO ANYONE		
BUSINESS CALENDAR	A PRE LOADED BUSINESS CALENDAR IS AVAILABLE YOU CAN SET SCHEDULES AND SYNCHRONIZE WITH		

BUILT-IN APPS

Everything you need to schedule meetings, manage e-mails, save and open files with the cloud and work on documents, all with Newline's built-in apps. Collaborate locally and remotely, easily

















CHENNAI

Door Nos:684 to 690, Unit No 3B2, 10th Floor,

Seethakathi Business Centre, Thousand Lights, Stellar, Sindhu Bhavan Road, Thaltej, DLF Tower A, Jasola District Centre, Anna Salai, Chennai - 600 006.

GUJARAT

104, 1st Floor, Shilp Arista, Opposite Unit No. A-717, 7th Floor, Ahmedabad 380015, Gujarat

DELHI

New Delhi- 110025

KOLKATA

RAIKVA Tower 3A, Ram Mohan Mullick Garden Lane, 3rd Floor, Suit No - 309 Kolkata, West Bengal 700010

HiteVision

MUMBAI

1st Floor, B-107, Kanakia Wall Street, Chakala, Andheri Kurla Road,

Andheri East Mumbai-400059, Maharashtra.

