

DV ONE+

With Digital Signage Software

Available Sizes

135" 163"
189" 216"

DEPARTURES 18:02					DEPARTURES 18:03				
TIME	DESTINATION	FLIGHT	GATE	REMARKS	TIME	DESTINATION	FLIGHT	GATE	REMARKS
18:08	NEW YORK	AC 103	13	CANCELLED	18:08	NEW YORK	AC 103	13	GATE CLOSING
18:16	BERLIN	CI5723	22	CANCELLED	18:16	BERLIN	CI5723	22	GATE CLOSING
18:38	LONDON	MU5984	12	CANCELLED	18:38	LONDON	MU5984	12	BOARDING
18:49	TOKYO	JL 608	14	DELAYED	18:49	TOKYO	JL 608	14	BOARDING
19:07	HONG KONG	CX6471	25	CANCELLED	19:07	HONG KONG	CX6471	25	ON TIME
19:18	MADRID	IB3941	03	DELAYED	19:18	MADRID	IB3941	03	DELAYED
19:29	SYDNEY	LH5021	17	CANCELLED	19:29	SYDNEY	LH5021	17	ON TIME
19:35	TORONTO	KA 197	11	CANCELLED	19:35	TORONTO	KA 197	11	ON TIME
19:44	PARIS	AF5870	02	DELAYED	19:44	PARIS	AF5870	02	DELAYED
19:50	ROME	FM 324	04	CANCELLED	19:50	ROME	FM 324	04	CANCELLED



ALL NEW

Fine Pixel Pitch

1.56 mm – for sharp clarity even at close viewing distances

Brightness & Contrast

550 nits' brightness and 6000:1 contrast ratio – vivid visibility in any lighting

Full HD Resolution

1920 x 1080 resolution across all sizes

Smooth Visuals

3840Hz refresh rate – ideal for motion clarity and video performance

Built-in Android 13

Optimized with the A311D2 chipset for seamless performance

Pro-AV Integration Ready

RS-232, IP Control, Wake-on-LAN, Wake-on-Wi-Fi

Color Accuracy

110% NTSC color gamut – vibrant, true-to-life colors

Front Serviceable Design

Modules are front-accessible for efficient maintenance

Remote Management

Compatible with Newline Display Management (NDM)

Professional Aesthetics

Ports concealed behind magnetic covers for a clean look

MODEL	DV-13524-PLUS	DV-16324-PLUS	DV-18924-PLUS	DV-21624-PLUS
DISPLAY				
Size	135"	163"	189"	216"
Lights Welding Type	SMD+GOB	SMD+GOB	SMD+GOB	SMD+GOB
Resolution	1920*1080	1920*1080	1920*1080	1920*1080
Aspect Ratio	16:9	16:9	16:9	16:9
Contrast Ratio	6000:1	6000:1	6000:1	6000:1
Refresh Rate	3840Hz	3840Hz	3840Hz	3840Hz
Typ. Max. Brightness	550 nits	550 nits	550 nits	550 nits
Color Gamut	NTSC 110%	NTSC 110%	NTSC 110%	NTSC 110%
Pixel Type	RGB	RGB	RGB	RGB
Viewing Angle	160°	160°	160°	160°
Color Depth	8 bit	8 bit	8 bit	8 bit
Grayscale Rating	14 bit	14 bit	14 bit	14 bit
Pixel Pitch	1.56mm	1.875mm	2.08mm	2.34mm
Display Area (mm)	3000*1687.5	3600*2025.5	4200*2362.5	4800*2699.7
Display Area (inch)	118.11*66.44	141.73*79.74	165.35*93.03	188.98*106.29
Outer Dimension (mm) (Including mounting bracket)	3009*1704*71	3609*2042*71	4209*2379.5*71	4809*2716.9*71
Outer Dimension (inch)	118.46*67.09*2.60	142.09*80.39*2.60	165.71*93.68*2.60	189.33*114.84*2.60
SMART SYSTEM				
Chipset	A311D2	A311D2	A311D2	A311D2
RAM	4GB	4GB	4GB	4GB
ROM	32GB	32GB	32GB	32GB
Wake-on-LAN	YES (Turn Off Mode)			
Wake-on-WiFi	YES (Turn Off Mode)			
OS Version	Android 13	Android 13	Android 13	Android 13
Speaker	Max. 5W x 1			
Input Voltage	100~204V 50/60Hz	100~204V 50/60Hz	100~204V 50/60Hz	100~204V 50/60Hz
Power Required	135" - 2	163" - 2	189" - 3	216" - 3
Power Consumption (Standby)	<0.5W <2W when WOL&WOW	<0.5W <2W when WOL&WOW	<0.5W <2W when WOL&WOW	<0.5W <2W when WOL&WOW
Power Consumption (Avg.)	135" - 580W	163" - 690W	189" - 880W	216" - 1000W
Power Consumption (Max.)	135" - <2000W	163" - <2100W	189" - <2800W	216" <4100W
WiFi	Wi-Fi 5 & 6 (2.4G + 5G)			
I/O PORTS				
Side I/O	1 x USB 3.0 Type A 1 x USB 2.0 Type B 1 x HDMI In 1 x Type C In(PD 65W)	1 x USB 3.0 Type A 1 x USB 2.0 Type B 1 x HDMI In 1 x Type C In(PD 65W)	1 x USB 3.0 Type A 1 x USB 2.0 Type B 1 x HDMI In 1 x Type C In(PD 65W)	1 x USB 3.0 Type A 1 x USB 2.0 Type B 1 x HDMI In 1 x Type C In(PD 65W)
Rear I/O Ports	1 x HDMI In 1 x HDMI Out 1 x USB 3.0 Type A 1 x Line Out 1 x S/PDIF Out 1 x LAN In 1 x RS232	1 x HDMI In 1 x HDMI Out 1 x USB 3.0 Type A 1 x Line Out 1 x S/PDIF Out 1 x LAN In 1 x RS232	1 x HDMI In 1 x HDMI Out 1 x USB 3.0 Type A 1 x Line Out 1 x S/PDIF Out 1 x LAN In 1 x RS232	1 x HDMI In 1 x HDMI Out 1 x USB 3.0 Type A 1 x Line Out 1 x S/PDIF Out 1 x LAN In 1 x RS232
Net Weight	152 Kgs	209.5 Kgs	340.0Kgs	TBC
Gross Weight (Not including pallet & wooden frame)	183 Kgs	260.5 Kgs	392.5Kgs	TBC
Packaging Dimension (mm)	2018*768*834	2254*768*1074	2598*768*1164	2300*1150*1167
Operating Temperature	0°C ~ 40°C (32°F ~ 104°F)			
Storage Temperature	0°C ~ 40°C (32°F ~ 104°F)			
Operating Humidity	10% ~ 90% no condensation			
Storage Humidity	10% ~ 90% no condensation			
Lifespan	100000 hours	100000 hours	100000 hours	100000 hours