

POWERFUL, PROFESSIONAL, ALWAYS ON....

With
Digital
Signage
Software



All New

STV 115+

with Newline Signage Pro

High Performance Pro Series TV



High
Performance



IP
Control



4K UHD &
Pure Color



Enhanced
Android 14



Ultra-thin
1.2mm Bezel



Digital
Signage



24/7
Operation

Newline Signage Pro

Newline Signage Pro is an advanced digital signage software that simplifies content management with an all-in-one online portal to control media, layouts, and user access.

- ✓ Digital Signage Software suited for Hospitals, Corporates, Restaurants, Malls etc
- ✓ Youtube, Twitter, RSS Live feeds
- ✓ Upto 6 layouts possible.
- ✓ Single Sign On (SSO) with Google and Microsoft
- ✓ Centralized Management & Control.



Comprehensive
Online Admin portal



Streamline Registration
Process & Device grouping



Fully Integrated
with Q Pro & STV+



Simple Scheduling &
Auto Launch



Versatile
pre-defined Layouts



User-Friendly Content Creation &
Customizable Text Formatting



Rich Content Support
With Live Feed Integration



Google Slides, Calender &
Canva Integration

STV+ SERIES STV-11524-PLUS

DISPLAY	
Active Screen Size	115"
Screen Type	LCD (Direct LED Backlight)
Display Area	2534 x 1425mm
Display Ratio	16:9
Resolution	3840 x 2160 (4K)
Refresh Rate	120Hz
Colors	1.07Billion
Color Depth	10bit+FRC
Brightness	750 nits
Typ. Static Contrast Ratio	18000:1
Viewing Angle	178°
Display Life Time	50000 hours
OC Haze	2.1%(typ) ,2.5%(max)
Display Orientation	Landscape only
Operation Time	24 hours x 7 days

SMART SYSTEM	
Chipset	MTK9679
CPU	ARM Cortex A73 x 4
GPU	ARM Mali-G52 MC1
RAM	4 GB
ROM	16 GB
Android Version	Android 14
OS Version	AOSP
WiFi Module	onboard
WiFi Version	WiFi 5
Bluetooth	BT5.0
Wake-on-LAN	Yes
Wake-on-WiFi	Yes
IP & RS232 Control	Yes
RTC	Support

AV PORTS	
Rear I/O	3 x HDMI In
Rear I/O	1 x USB 3.0 Android
Rear I/O	1 x USB 2.0 Android
Rear I/O	1 x S/PDIF Out
Rear I/O	1 x Line Out
Rear I/O	1 x RS232
Rear I/O	1 x LAN In (100M)
Rear I/O	1 x AV In

SOUND	
Speaker Position	Bottom + Surround + Sky + Subwoofer
Speaker Power (Max.)	Sky: L + R 2*10W SR: R1+R2 \ L1+L2 4*10W Bottom: L + R 2*10W Subwoofer:20W*2
Speaker Rated Impedance	6Ω
Speaker Freq.Response	Sky ~ 200 ~ 20K Hz SR:200 ~ 20K Hz
Output S.P.L.	Sky ~ 73dB SR:77dB

ELECTRONIC CAPACITY	
Working Voltage	AC100-240V
Working Power Consumption (Normal)	≤700w
Working Power Consumption (Full Load)	≤1000W
Power Consumption (Standby Mode)	≤0.5W
Power Consumption(Wake-on-LAN or Wake on-WiFi)	<2W

STRUCTURE	
Outline Dimension (without wall mount bracket)	2564.6 x 1468.6 x 61.7 mm
Bezel Width (T/L/R)	1.5/1.5/1.5mm
Bottom Bezel Width	14.7mm
Bottom Bezel Width Including IR Receiver	21.7

TRANSPORTATION & STORAGE	
Storage Temperature & Humidity	-20~60°C 0~90%RH (non-condensing)"
Working Temperature/ Humidity	0~40°C 20~80%RH (non-condensing)
Installation Method (optional)	wall-mounted / landing leg
Packing Dimension	2780*280*1680mm
VESA Mount Pattern	553X1000X553mm
Net Weight	94.3kg
Gross Weight	131.5kg



newline

1-800-419-0309
www.newlineinteractive.in