

newline

# All-In-One Collaboration Solution

High  
Performance  
Touch + UC  
Environment



# THE NEXT GENERATION OF COLLABORATION IS HERE **Z** **S E R I E S**

WITH THIS **FULL HYBRID** SOLUTION

WHITEBOARD

CAST

BROADCAST

ENGAGE

APP STORE

CLASSROOM TOOLS

DISPLAY MANAGEMENT

# PRODUCT SPECIFICATIONS

# Z SERIES

MODEL	TT-5522Z	TT-6522Z	TT-7522Z	TT-8622Z
<b>DISPLAY</b>				
Active Screen Size	55"	65"	75"	86"
Backlight	DLED	DLED	DLED	DLED
Display Area (mm)	1210 x 680 mm	1428 x 803 mm	1650 x 928 mm	1895 x 1066mm
Display Ratio	16:9	16:9	16:9	16:9
Resolution	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)	3840 x 2160 (4K)
Colors	1.07Billion ( 10 bit color )	1.07Billion ( 10 bit color )	1.07Billion ( 10 bit color )	1.07Billion ( 10 bit color )
Brightness	400 cd/m <sup>2</sup>	450 cd/m <sup>2</sup>	450cd/m <sup>2</sup>	500 cd/m <sup>2</sup>
Contrast Ratio	4000:1	15000:1	15000:1	15000:1
Response Time	4ms	4ms	4ms	4ms
Viewing Angle	H = 178, V = 178 typ.	H = 178, V = 178 typ.	H = 178, V = 178 typ.	H = 178, V = 178 typ.
Display Life Time (MTBF)	≥50000 hours	≥50000 hours	≥50000 hours	≥50000 hours
<b>ELECTRICAL</b>				
Working Voltage	AC100-240V Max 2.5A	AC100-240V Max 4.0A	AC100-240V Max 5.0A	AC100-240V Max 5.5A
Power Consumption (Eco mode)	<150W	<188W	<240W	<270W
Power Consumption (Standby mode)	<0.5W	<0.5W	<0.5W	<0.5W
<b>TOUCH</b>				
Touch Surface Material	Metal Mesh	Metal Mesh	Metal Mesh	Metal Mesh
Glass Surface Technology	AntiGlare+Anti-Fingerprint Tempered Glass	AntiGlare+Anti-Fingerprint Tempered Glass	AntiGlare+Anti-Fingerprint Tempered Glass	AntiGlare+Anti-Fingerprint Tempered Glass
	Antimicrobial Tempered Glass	Antimicrobial Tempered Glass	Antimicrobial Tempered Glass	Antimicrobial Tempered Glass
Touch Surface	Optical Bonding	Optical Bonding	Optical Bonding	Optical Bonding
Touch Sensor	Projective Capacitive (PCAP)	Projective Capacitive (PCAP)	Projective Capacitive (PCAP)	Projective Capacitive (PCAP)
Transparency	88%±3	88%±3	88%±3	88%±3
Haze	2%~5%	2%~5%	2%~5%	2%~5%
Touch Surface Hardness	7H	7H	7H	7H
HID Support	Yes	Yes	Yes	Yes
Touch Points	20 Point/ optional Windows 40Point	20 Point/ optional Windows 40Point	20 Point/ optional Windows 40Point	20 Point/ optional Windows 40Point
Touch Screen Writing Tools	Passive pen/ Fingers	Passive pen/ Fingers	Passive pen/ Fingers	Passive pen/ Fingers
Positioning Accuracy	±1mm	±1mm	±1mm	±1mm
<b>SPEAKER</b>				
Speaker Position	Top-front	Top-front	Top-front	Top-front
Speaker Rated Impedance	6Ω	6Ω	6Ω	6Ω
Speaker Freq.Response	180Hz-20KHz when SPL is -10dB	180Hz-20KHz when SPL is -10dB	180Hz-20KHz when SPL is -10dB	180Hz-20KHz when SPL is -10dB
Output S.P.L.	0dB~ -10dB	0dB~ -10dB	0dB~ -10dB	0dB~ -10dB
Speaker Max.Power Output	20Wx2 + 15W Subwoofer	20Wx2 + 15W Subwoofer	20Wx2 + 15W Subwoofer	20Wx2 + 15W Subwoofer
<b>MICROPHONE</b>				
Mic Position	8-mic array - upper front	8-mic array - upper front	8-mic array - upper front	8-mic array - upper front
Distance	8m	8m	8m	8m
<b>CAMERA MODULE</b>				
Camera Resolution	4K@ 30 Hz /UHD	4K@ 30 Hz /UHD	4K@ 30 Hz /UHD	4K@ 30 Hz /UHD
Field of View	120° FOV Lenses	120° FOV Lenses	120° FOV Lenses	120° FOV Lenses
Camera Tile Range	15°	15°	15°	15°
<b>TRANSPORTATION / STORAGE</b>				
Storage Temperature/Humidity	-20~60°C & 0~90%RH (non-condensing)	-20~60°C & 0~90%RH (non-condensing)	-20~60°C & 0~90%RH (non-condensing)	-20~60°C & 0~90%RH (non-condensing)
Working Temperature/Humidity	0~40°C & 20~80%RH (non-condensing)	0~40°C & 20~80%RH (non-condensing)	0~40°C & 20~80%RH (non-condensing)	0~40°C & 20~80%RH (non-condensing)
Installation Method (optional)	wall-mounted / mobile stand	wall-mounted / mobile stand	wall-mounted / mobile stand	wall-mounted / mobile stand
Outline Dimension <small>(without wall mount bracket thickness)</small>	1278.1 x 798.4 x 79.8 mm	1497.1 x 919.6 x 83.8 mm	1719.3 x 1043.7 x 85 mm	1965.2 x 1184.4 x 85 mm
Packing Dimension	1414 x 185 x 915 mm	1640 x 207 x 1036 mm	1859 x 227 x 1160 mm	2119 x 250 x 1290 mm
Net Weight	28 kg	36 kg	50 kg	60 kg
Gross Weight	36 kg	46.5 kg	64 kg	76 kg
<b>SMART SYSTEM</b>				
SoC Chipset	Amlogic 311D2	Amlogic 311D2	Amlogic 311D2	Amlogic 311D2
RAM	8GB	8GB	8GB	8GB
Flash Memory	64GB	64GB	64GB	64GB
Android Version	Android 11	Android 11	Android 11	Android 11
Multimedia File Formats Support	*Image: JPEG, BMP, PNG Video: MPEG1, MPEG2, MPEG4, Sorenson H.263, H.263, H.264, HEVC/H.265, MVC, AVS, AVS+, WMV3, VC1, Motion JPEG,VP8, VP9, RV30/RV40 Audio:MPEG1/2 @LAYER1,@LAYER2,@LAYER3, EAC3, ACC-LC, HE-AAC, VORBIS, LPCM, IMA-ADPCM, MS-ADPCM, G711 A/MU-LAW, LBR(COOK), FLAC"			
<b>SIDE I/O</b>				
USB Type-C (PD 65W/100W Optional)	1	1	1	1
HDMI IN 2.0	1	1	1	1
USB Type-B (Touch)	1	1	1	1
USB 3.0 Type-A	1	1	1	1
Microphone In	1	1	1	1
<b>REAR I/O</b>				
HDMI IN 2.0	2	2	2	2
DisplayPort 1.2	1	1	1	1
USB Type-B (Touch)	3	3	3	3
USB 3.0 Type-C (no PD)	1	1	1	1
USB 3.0 Type-A	2	2	2	2
USB 3.0 Type-A to Android	1	1	1	1
HDMI OUT 2.0	1	1	1	1
RS232	1	1	1	1
RJ45 (Gigabit)	IN*1 & OUT*1	IN*1 & OUT*1	IN*1 & OUT*1	IN*1 & OUT*1
OPS	1	1	1	1
SPDIF	1	1	1	1
Audio Line out	1	1	1	1
WIFI module	1	1	1	1
Proximity Sensor	1	1	1	1
SDM-S Slot	N/A	Yes	Yes	Yes

## newline



1-800-419-0309

www.newlineinteractive.in

Chennai

Room No. 202, 203, 211  
No.37, Workafella, TTK Road, Alwarpet,  
Chennai-600018, Tamil Nadu

Gujarat

104, 1st Floor, Shilp Arista, Opposite  
Stellar, Sindhu Bhavan Road, Thaltej,  
Ahmedabad 380015, Gujarat

Delhi

Unit No. A-717, 7th Floor,  
DLF Tower A, Jassola District Centre,  
New Delhi- 110025

Kolkata

RAIKVA Tower 3A, Ram Mohan  
Mullick Garden Lane, 3rd Floor, Suit No - 309  
Kolkata, West Bengal 700010

Mumbai

1st Floor B-107, Kanakia Wall Street,  
Chakala, Andheri Kurli Road,  
Andheri East Mumbai-400059, Maharashtra.